



**4AA PROPOLYMER® LED
DIV 1/DIV 2 ALKALINE
BATTERY-POWERED FLASHLIGHT**



Material/Lens Engineering polymer resin that is virtually indestructible, shock-resistant, non-conductive, and lightweight. Unbreakable polycarbonate lens with scratch-resistant coating.

Dims/Weight	IMPERIAL	Length: 6.5 in	Width: 1.34 in	Diameter: 1.63 in	Weight: 6.3 oz
	METRIC	Length: 16.51 cm	Width: 3.40 cm	Diameter: 4.14 cm	Weight: 178.6 g

Light Source/Output White LED, impervious to shock with a 50,000-hour lifetime. Deep parabolic reflector produces long-range brilliance and smooth uniform beam pattern. Optimized electronics provide maximum light output throughout battery life.

Output/Runtime:	LUMENS	67
	RUN TIME	155 hours

Switch Push-button tail switch provides one-handed momentary or constant operation.

Battery Four (4) "AA" alkaline batteries (included)

- Features**
- IP67-rated design; waterproof to 1 meter for 30 minutes
 - 1-meter impact resistance tested
 - Non-conductive
 - Corrosion-proof

Approvals

Division 1:
Class I, Div. 1, Groups C, D Class I, Div 2, Groups A, B, C, D Class II, Div. 2, Group F, G Class III, T3C

Division 2:
Class I, Div. 2, Groups A, B, C, D Class II, Div. 2, Group F, G Class III, T3C

MSHA Permissible Flashlight, Approval No. 10C-658-0 Tested for Intrinsic Safety in Methane-Air mixtures only
(Approved for use with Energizer E91, Duracell MN1500 and Rayovac 815)

Meets applicable United Kingdom & European Community Directives.

Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2-year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Description	UPC	Item #
4AA ProPolymer LED with alkaline batteries - Blister - Yellow	080926-68202-3	68202
4AA ProPolymer LED with alkaline batteries - Blister - Black	080926-68302-0	68302
4AA ProPolymer LED with alkaline batteries - Box - Yellow	080926-68201-6	68201
4AA ProPolymer LED with alkaline batteries - Box - Black	080926-68301-3	68301
4AA ProPolymer LED without alkaline batteries - Box - Yellow	080926-68200-9	68200
4AA ProPolymer LED without alkaline batteries - Box - Black	080926-68300-6	68300

	Description	UPC	Item #
	4AA/3AA Helmet Mount	080926-68085-2	68085
	4AA/3AA Gallet Mount	080926-68086-9	68086
	Polymount Kit	080926-68089-0	68089
	Rubber Helmet Strap	080926-99075-3	99075
	3AA / 4AA ProPolymer Series Belt Clip	080926-68088-3	68088
	Lanyard with Push-Button Slide	080926-72024-4	72024
	Nylon Holster	080926-68905-3	68905
	Safety Wand - Blue	080926-75902-2	75902
	Safety Wand - Red	080926-75903-9	75903
	Safety Wand - Yellow	080926-75904-6	75904
	Safety Wand - White	080926-75908-4	75908
	Safety Wand - Glow-in-the-dark	080926-75913-8	75913

4AA PROPOLYMER® LED
SAFETY-RATED ALKALINE BATTERY POWERED FLASHLIGHT

DESCRIPTION: The 4AA ProPolymer® LED is an intrinsically safe, high-performance, 4 “AA” alkaline-powered flashlight. It features a soft flood light with seven (7) ultra-bright white LEDs. The body is constructed of an engineering polymer resin that is virtually indestructible, shock-resistant, non-conductive, and lightweight.

CASE MATERIAL: Impact-resistant engineering polymer resin. Available in black or high-visibility yellow.

DIMENSIONS: Length: 6.50 in (16.51 cm) Width: 1.34 in (3.40 cm) Face cap diameter: 1.63 in (4.14 cm)

WEIGHT: 6.3 oz (178.6 g) with batteries (included with purchase)

LENS: Unbreakable polycarbonate lens with scratch-resistant coating

LIGHT SOURCE: 7 ultra-bright white LED, impervious to shock with a 50,000-hour lifetime


LIGHT OUTPUT: 67 lumens


ON/OFF: Push-button tail switch provides one-handed momentary or constant on operation


RUN TIME: 155 hours

BATTERY: Four (4) “AA” size alkaline batteries

FEATURES: 7 ultra-bright white LEDs
Waterproof
Non-conductive
Corrosion-proof
Wrist lanyard connection

APPROVALS*:  Class I, Div. 1, Groups C, D
Class I, Div 2, Groups A, B, C, D
Class II, Div. 2, Group F, G
Class III, T3C

 Class I, Div. 2, Groups A, B, C, D
Class II, Div. 2, Group F, G
Class III, T3C

 Permissible Flashlight, Approval No. 10C-658-0
Tested for Intrinsic Safety in Methane-Air mixtures only
(Approved for use with Energizer E91, Duracell MN1500 and Rayovac 815)

 Meets applicable United Kingdom and European Community Directives

WARRANTY: Streamlight’s Limited Lifetime Warranty

OPTIONAL ACCESSORIES: Helmet clamps, traffic wand, holster

* See product for specific ratings.