

Increased output with added features, the C1D1 safety rated Survivor X right-angle light is available as a fully rechargeable system or an economical alkaline model that provides a 25% cost savings on batteries.



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation



No tools needed to change batteries



Rubber dome push-button switch easy to use with gloves
Features battery life indicator

Battery life indicator in switch:
 – Green indicates full charge
 – Turns red when battery is nearing low voltage
 – Flashes red continuously when 15 minutes left of battery life

Unbreakable polycarbonate lens with silicone anti-scratch coating
Specialized optic combines low profile with strong performance and a wide beam

Rugged nylon polymer body is virtually indestructible

New charger design:

- Survivor X securely locks into the charger - fits snugly in place
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands



High, low and emergency flash modes:

- High for a super-bright, smoke piercing beam: 250 lumens; 447m beam distance; runs 3.75 hours (Li-Ion); runs 5 hours (alkaline)
- Low for longer run time: 60 lumens; 237m beam distance; runs 15 hours (Li-Ion); runs 15 hours (alkaline)
- Flash for signaling: runs 8 hours

Optimized electronics provide regulated intensity

IP67 rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested

Uses rechargeable lithium ion battery (charges in 5 hours) or three alkaline batteries

7.06 in. (17.92 cm); Li-Ion: 12.2 oz (346g); Alkaline: 12.8 oz (363g)

Class I & II, Division 1, Groups A,B,C,D,E,F,G; Class III, T-Code: T3/T4

Flashlight meets 500°F requirements of NFPA 1971-8.6 (2013)

Charger meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position

Limited Lifetime Warranty

Visit streamlight.com for full warranty information

Description	Orange	Yellow
Survivor X - 120V/100V AC/12V DC	#90952	#90962
Survivor X - 230V AC/12V DC	#90953	#90963
Survivor X - Alkaline	#90950	#90960
Survivor X - Light Only	#90951	#90961



SURVIVOR® X C1D1 SAFETY RATED RIGHT-ANGLE FLASHLIGHT



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation



Battery life indicator in switch:
 – Green indicates full charge
 – Turns red when battery is nearing low voltage
 – Flashes red continuously when 15 minutes left of battery life



New charger design:
 – Survivor X securely locks into the charger - fits snugly in place
 – Quick release latch for one-handed grab-and-go
 – Easy to remove with gloved hands

- Material/Lens** Housing, base and battery housing made from high impact super tough nylon offering exceptional durability. All openings are O-ring sealed for IP67 waterproofing. Spring-loaded clip with built in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One way valve for case venting.
- Dims/Weight** Height: 7.06 in.; Height in charger: 8.67; Width: 2.85 in.; Diameter: 2.32 in.; Grip area: Height:3.60 in.; Thickness: 1.35 in.; Width: 2.20 in. Weight: 346g (with lithium ion); 363g (with AA Alkaline)
- Light Source** White LED impervious to shock with a 50,000 hour lifetime
 Custom "Total Internal Reflection" optic for narrow beam and optimum peripheral illumination. Optional insertable black plug reduces peripheral illumination for improved smoke cutting ability or amber plug reduces eye fatigue.
- Output/Run time** Three lighting modes:
 • High for a super-bright, smoke piercing beam: 250 lumens; 447m beam distance; 50,000 candela; runs 3.75 hours (Li-Ion); runs 5 hours (alkaline);
 • Low for longer run time: 60 lumens; 237m beam distance; 14,000 candela; runs 15 hours (Li-Ion); runs 15 hours (alkaline)
 • Flash for signaling: runs 8 hours continuous
- Switch** Push button switch designed for extremely long life.
 Translucent rubber dome push button actuator provides easy operation even when wearing heavy gloves.
- Battery/Charging** 2.6Ahr Li-Ion Battery pack fully charges in 5 hours.
 The translucent switch boot contains an integrated red/green battery status indicator.
 Charger indicator turns red when charging, turns green when fully charged.
The Survivor® X is not compatible with legacy Survivor® chargers.
- INDICATOR:**
 Solid green for 5 seconds: Battery is ready for use.
 Solid red: 45 minutes of battery life remaining.
- Features**
- Reduced bezel length to minimize snag hazards
 - D-ring provides forward hanging orientation
 - Updated battery door design for improved operation and seal.
 - IP67 rated; dust-tight and waterproof to 1m for 30 minutes; 2m impact resistance tested
 - Strong Spring-loaded clip grabs onto belts and gear
- Approvals** Class I & II, Division 1, Groups A,B,C,D,E,F,G; Class III, T-Code: T3/T4
 Flashlight meets 500°F requirements of NFPA 1971-8.6 (2013)
 Charger meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.



Description	Orange		Yellow	
	UPC	ITEM#	UPC	ITEM#
Survivor X - 120V/100V AC/12V DC	080926-90952-6	#90952	080926-90962-5	#90962
Survivor X - 230V AC/12V DC	080926-90953-3	#90953	080926-90963-2	#90963
Survivor X - Alkaline	080926-90950-2	#90950	080926-90960-1	#90960

90910
90911
90912



90345



90341



90342



Description	UPC	Item #
120V/100V AC Bank Charger - Survivor X	080926-90910-6	90910
230V AC Bank Charger - Survivor X	080926-90911-3	90911
12V DC Bank Charger - Survivor X	080926-90912-0	90912
Charger Holder - Survivor X	080926-90345-6	90345
Lithium Ion Battery - Survivor X C1D1	080926-90341-8	90341
Battery Carrier - Survivor X (for alkaline or SL-B26 models)	080926-90342-5	90342
Smoke Cutter® Plug Kit*		908019

* image not available