

The multi-function, C1D1 safety-rated Survivor Pivot features a dual-beam and 90-degree articulating head. Its spot beam uses a cool white, high-power LED for maximum distance illumination and its flood beam is angled downward for area illumination.



Option with magnet available
(as shown to the right below)



Strong spring-loaded clip securely grabs onto belts and gear; D-ring provides forward hanging orientation



- Survivor Pivot securely locks into the charger
- Quick release latch for one-handed grab-and-go
- Easy to remove with gloved hands

90° articulating head

Spot beam with a cool white LED for distance lighting

Downward angled flood beam for area illumination



- Battery status indicator in switch:
- Green indicates full charge
 - Turns red when battery is nearing low voltage
 - Flashes red continuously when 15 minutes left of battery life

No tools needed to change batteries

Rugged nylon polymer body is virtually indestructible



Spot: High: 300 lumens; 369m beam distance; runs 4.25 hours (Li-Ion); runs 5.5 hours (alk) Low: 70 lumens; 184m beam distance; runs 16 hours (Li-Ion); runs 15 hours (alk)	
Flood: High: 300 lumens; 35m beam distance; runs 4.25 hours (Li-Ion); runs 5.5 hours (alk) Low: 70 lumens; 17m beam distance; runs 16 hours (Li-Ion); runs 15 hours (alk)	
Combo: High: 325 lumens; 276m beam distance; runs 3.75 hours (Li-Ion); runs 4.5 hours (alk) Low: 80 lumens; 141m beam distance; runs 13 hours (Li-Ion); runs 12 hours (alk)	
Uses rechargeable lithium-ion battery pack (charges in 5 hours) or three (3) alkaline batteries (requires optional battery carrier)	
Non-Magnet: Li-Ion: 16.2 oz (459 g) Alkaline: 16.7 oz (473 g) Magnet: Li-Ion: 16.6 oz (471 g) Alkaline: 17.1 oz (485 g)	
Height: 7.93 in (20.1 cm); Width: 2.86 in (7.26 cm) Thickness: 3.29 in (8.36 cm); Thickness (w/ magnet): 3.64 in (9.25 cm)	

Unbreakable polycarbonate lens with scratch-resistant coating				
Class I & II, Division 1, Groups A,B,C,D,E,F,G; Class III, T-Code: T3/T4 Flashlight meets 500°F requirements of NFPA 1971-8.6 (2013) Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position				
IPX7-rated; waterproof to 1m for 30 minutes				
Limited Lifetime Warranty Visit streamlight.com for full warranty information				
Description	Orange w/o Magnet	Yellow w/o Magnet	Orange w/ Magnet	Yellow w/ Magnet
Survivor Pivot - 120V/100V AC/12V DC	#91802	#91812	#91830	#91831
Survivor Pivot - 230V AC/12V DC	#91803	#91813	#91832	#91833
Survivor Pivot - Alkaline	#91800	#91810	#91825	#91826


 Pictured **without** magnet option

 Pictured **with** magnet option


Material/Lens: Housing, base, and battery housing made from high-impact, super tough polymer offering exceptional durability. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting. Available in orange and high-visibility yellow.

Dims/Weight:

	HEIGHT: 7.93 in	WIDTH: 2.86 in	THICKNESS: 3.29 in	THICKNESS w/ MAGNET: 3.64 in
IMPERIAL	WEIGHT w/o MAGNET LI-ION: 16.2 oz	WEIGHT w/o MAGNET ALKALINE: 16.7 oz	WEIGHT w/ MAGNET LI-ION: 17.6 oz	WEIGHT w/ MAGNET ALKALINE: 18.1 oz
METRIC	HEIGHT: 20.14 cm	WIDTH: 7.26 cm	THICKNESS: 8.36 cm	THICKNESS w/ MAGNET: 9.25 cm
	WEIGHT w/o MAGNET LI-ION: 459 g	WEIGHT w/o MAGNET ALKALINE: 473 g	WEIGHT w/ MAGNET LI-ION: 499 g	WEIGHT w/ MAGNET ALKALINE: 513 g

Light Source: Spot: Custom "Total Internal Reflection" (TIR) optic for narrow beam and optimum peripheral illumination
 Flood: Unique bias reflector provides maximum area illumination

**Output/
Run Time:**

	COMBO		SPOT		FLOOD	
	HIGH	LOW	HIGH	LOW	HIGH	LOW
LUMENS:	325	80	300	70	300	70
CANDELA:	19,000	5,000	34,000	8,500	300	75
DISTANCE:	276 m	141 m	369 m	184 m	35 m	17 m
RUN TIME LI-ION:	3.75 hours	13 hours	4.25 hours	16 hours	4.25 hours	16 hours
RUN TIME ALKALINE:	4.5 hours	12 hours	5.5 hours	15 hours	5.5 hours	15 hours

Switch: Ultrasonic welded switch designed for extremely long life. Rubber dome push-button actuator provides easy operation, even when wearing heavy gloves. Translucent switch boot contains an integrated red/green battery status indicator
 - Solid green for 5 seconds: Light is charged and ready for use
 - Solid red: 45 minutes or less of battery life remaining
 - Flashing red: 15 minutes or less of battery life remaining

Battery: - 2.6 Ahr Li-Ion battery pack fully charges in 5 hours. Battery status indicator shows red when charging; turns green when fully charged.
 - Three (3) optional AA alkaline batteries

Features: - Simultaneous spot and flood mode for maximum illumination
 - Translucent switch boot with integrated battery status indicator
 - Charge cradle designed for one-handed light removal
 - Multi-fuel design; accepts multiple battery types
 - IP67-rated; dust-tight and waterproof to 1m for 30 minutes;
 - 2m impact resistance tested
 - Strong spring-loaded clip grabs onto belts and gear
 - Magnet option

Approvals: Class I & II, Division 1, Groups A, B, C, D, E, F, G; Class III, T-Code: T3/T4
 T-CLASS T4 only: Streamlight 90341, Duracell MN1500, Varta 4006, Energizer EN91
 T-CLASS T3 only: Streamlight 90340

Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018).
 Charging rack meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.
 CEC Compliant.
 Meets applicable United Kingdom and European Community Directives.

Warranty: Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace, or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches, and electronics which have a 2-year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit streamlight.com for full warranty information.

Description	UPC	Item #	Description	UPC	Item #
ORANGE			ORANGE		
Survivor Pivot - 120V/100V AC/12V DC - Orange	080926-91802-3	91802	Survivor Pivot Magnet - 120V/100V AC/12V DC - Orange	080926-91830-6	91830
Survivor Pivot - 230V AC/12V DC - Orange	080926-91803-0	91803	Survivor Pivot Magnet - 230V AC/12V DC - Orange	080926-91832-0	91832
Survivor Pivot - Alkaline - Orange	080926-91800-9	91800	Survivor Pivot Magnet - Alkaline - Orange	080926-91825-2	91825
YELLOW			YELLOW		
Survivor Pivot - 120V/100V AC/12V DC - Yellow	080926-91812-2	91812	Survivor Pivot Magnet - 120V/100V AC/12V DC - Yellow	080926-91831-3	91831
Survivor Pivot - 230V AC/12V DC - Yellow	080926-91813-9	91813	Survivor Pivot Magnet - 230V AC/12V DC - Yellow	080926-91833-7	91833
Survivor Pivot - Alkaline - Yellow	080926-91810-8	91810	Survivor Pivot Magnet - Alkaline - Yellow	080926-91826-9	91826

Note: The Survivor Pivot® is not compatible with legacy Survivor® chargers.

	Description	UPC	Item #
	5-Unit 120V AC Bank Charger 5-Unit 230V AC Bank Charger 5-Unit 12V DC Bank Charger	080926-90910-6 080926-90911-3 080926-90912-0	90910 90911 90912
	Charger Holder	080926-90345-6	90345
	Battery Carrier (for alkaline or SL-B26® models) <i>Batteries not included</i>	080926-90342-5	90342
	Lithium-Ion Battery Pack - C1D1	080926-90341-8	90341
	12V DC1 Charge Cord	080926-22051-5	22051
	12V DC2 Charge Cord	080926-22050-8	22050
	120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V AC Charge Cord	080926-22062-1	22062
	Magnet Accessory Kit (<i>magnet only, clip not included</i>) - Survivor Pivot	080926-91840-5	91840